Developing and validating a multivariable prediction model for predicting costs of colon surgery

Anas Taha^{1,2,+}, Stephanie Taha-Mehlitz^{3,+}, Vincent Ochs^{1,} Bassey Enodien², Michael Drew Honaker⁴, Daniel M. Frey^{2,++} and Philippe C. Cattin^{1,++}

3

4

6 7	1. Department of Biomedical Engineering, Faculty of Medicine, University of Basel, Allschwill, Switzerland
8	2. Department of Surgery, GZO Hospital, Wetzikon, Switzerland
9 10	3. Clarunis, Department of visceral Surgery, University Center for Gastrotestinal and liver Diseases, St. Clara Hospital, Basel Switzerland
11 12	4. Department of Surgical Oncology and Colorectal Surgery, East Carolina University, Brody School of Medicine, Greenville, North Carolina, USA.
13	⁺ These authors contributed equally to this work and share the first authorship.
14	⁺⁺ These authors contributed equally to this work and share the last authorship.
15	
16	Correspondence: anas.taha@unibas.ch
17	
18	

19

20 Abstract

21 Hospitals are burdened with predicting, calculating and managing various cost-affecting 22 parameters regarding patients and their treatments. Accuracy in cost prediction is further affected 23 if a patient suffers from other health issues which hinder the traditional prognosis. This can lead 24 to an unavoidable deficit in the final revenue of medical centers. This study aims to determine 25 whether machine learning (ML) algorithms can predict cost factors based on patients undergoing 26 colon surgery. For the forecasting, multiple predictors will be taken into the model to provide a 27 tool that can be helpful for hospitals to manage their costs which ultimately will lead to operating 28 more cost-efficiently. . This proof of principle will lay the groundwork for an efficient ML-based 29 prediction tool based on multicenter data from a range of international centers in the subsequent 30 phases of the study. With a % MAPE result of 18 – 25.6, our model's prediction showed decent 31 results to forecast the costs regarding various diagnosed factors and surgical approaches. There 32 is an urgent need for further studies on predicting cost factors, especially for cases with 33 anastomotic leakage, to minimize unnecessary costs for hospitals.

34

35 1. Introduction

36 1.1 Background

37 Colorectal cancer (CRC)is one of the most prevalent cancers in the world today based on 38 diagnoses, with about 1.8 million cases being diagnosed and about 0.7 million related deaths 39 occurring annually. In addition, CRC accounts for 10% of all newly diagnosed cancers, a 40 considerable social and economic burden for many nations worldwide (1). One of the treatment 41 modalities for colorectal cancer is surgery. Surgery is aimed at obtaining an adequate oncologic 42 resection while re-establishing intestinal continuity. Over time, there have been improvements in 43 the way the disease is treated. But existing patien comorbidities can limit the surgical procedures. 44 The time required to prepare patients for surgery and address their comorbidities contribute to 45 increased surgical costs. However, despite many improvements, significant other complications 46 still occur during, and especially after, a surgical procedure. To avoid this, the patient is placed in necessary post-operative care, generally for 5 and 7 days after a surgical operation. Other post-47 48 operative risk factors will further add to the surgical cost, but their prediction is very vague due 49 to the absence of sufficient datasets. These involve performing a colorectal anastomosis, 50 anastomotic leak, (2), delirium or prolonged ileus (3), other emergency surgeries, longer intra-51 operative time, and peritoneal contamination

The comorbidities and longer stays result in a cost burden for patients and hospitals. This is why prediction models are now being updated to determine the costs for anastomotic insufficiency. Prediction models are normally used to estimate the probability of achieving a particular outcome (4). A large number of prediction models have been developed, but only a small number are used because not all models accurately predict the desired outcome (5). This

57 study focuses on developing and validating a multivariable prediction model to predict costs for

58 patients undergoing colon surgery while considering their stay in the hospital. This will help

59 determine the cost burden due to variable hospital length of stay (LOS) as well as days spent in

60 intensive care units (ICU). The medical context is prognostic in that it is focused on predicting

61 the cost of overall expenditure involved in colon surgery for the clinical center and the patient.

62 1.2 Rationale

63 The rationale for developing and validating the multivariable model is that it will help 64 accurately predict the costs associated with colon surgery. Accurate prediction will help patients 65 and practices employeed by the hospital make more informed decisions, as well as aid in policies enacted by the government. The results that come with the use of the model will also aid in 66 67 surgical planning. In short, developing and validating the multivariable model will provide insight into costs involved in colon surgery. In turn, it will allow revisions in care and help 68 69 develop strategies for improved management. Similar studies for prediction purposes have been 70 conducted in the field of medicine. For example, Musunuri et al. have used machine learning in 71 the form of artificial intelligence to predict 90-day liver disease mortality. Focused on acute-on-72 chronic liver failure, they achieved a model with an accuracy of 94.12% and an area under the 73 curve of 0.915 (6). Hameed et al. wrote about the impact of artificial intelligence on urological 74 diseases. In their literature review, they have pointed to multiple publications using various 75 models like support vector machine, nearest neighbour, random forrest, convolutional neural 76 network or artificial neural networks to predict and classify diseases like prostate cancer, 77 urothelial cancer, renal cancer or urolithiasis. What differs from those publications and their work 78 from ours is, that they use a classification model instead of a regression model. The most 79 important benefit of using a regression model compared to a classification model is that it helps 80 predict continuous values, whereas classification models try to predict discrete class labels. To 81 predict the costs associated with colon surgery in an accurate way, a machine learning regression 82 model is used. Using this approach. We aim to contribute to an existing gap in this field (7).

83 1.3 Objectives

84

- To develop prediction models for the final costs in patients based on multiple predictors.
- To test the models in terms of their ability to accurately predict the final costs associated
 with colon surgery in patients.

87 2. Methods

- 88 2.1 Overview and Data Collection
- 89 Data was extracted from a registry of patients who underwent colonic anastomosis for
- 90 various reasons such as tumors, diverticulitis, mesenterial ischemia, iatrogenic or traumatic
- 91 perforation, or inflammatory bowel disease (aggregated as "non-tumor") at the Hospital of
- 92 Wetzikon from 1st January 2013 to the 31st December of 2019. No patients were excluded from
- 93 the initial data collection. Furthermore, this study was completed based on the transparent
- 94 reporting of a multivariable prediction model for individual prognosis or diagnosis (TRIPOD)

- 95 statement checklist for prediction model development (8).
- 96 Utilizing this data, we developed a machine learning model to predict the costs of colon
- 97 surgery.
- 98 2.2 Ethical Considerations

99 The registry data was approved by an institutional review board, where the patients' 100 informed consent was waived. The study was registered at [Req 2021-01107].

101 2.3 Predictors and Outcome Measures

102 Recorded variables include Insurance (general/semi-private/private), age, surgical 103 procedure (Hartmann/left sided hemicolectomy and extended left sided hemicolectomy/ right 104 sided hemicolectomy and extended right sided hemicolectomy/sigmoid resection), surgical 105 approach (open/laparoscopic), diagnosis (tumor/non-tumor), final costs (the sum of all cost 106 factors), length of stay (in days), Intensive care stay (in days), operation time (in minutes), 107 anaesthesia time (in minutes), ASA-Score (I,II,III,IV), gender (male/female), CCI (Charlson 108 Comorbidity Index), anastomotic insufficiency and emergent/non-emergent. The data on the 109 final cost, which is the sum of all the costs incurred during the stay in hospital for surgery, were collected in CHF (Swiss Francs). Other cost factors not incorporated since they add up to the final 110 111 costs include administrative costs, costs of hospitality, nurse costs, costs of infrastructure, doctor 112 costs, medical costs, operational costs, anesthesia costs and care costs.

113 2.4 Model Development

Data was randomly split into two sets, 80% of the data was put into a training set to build the models and 20% was utilized for a test set to validate the models and assess their performance internally. The two sets had approximately the same class distribution (Gaussian). The following 14 predictors were chosen to predict the final costs based on regression and clinical insights: age, gender, insurance, diagnosis, operation, surgical approach, hospitalization, intensive care, surgical procedure and anaesthesia time, CCI, ASA-Score, anastomotic insufficiency and emergency surgery (9).

By having variables included, such as the CCI and the ASA-Score, we are able to cover a large number of diseases that are included in the comorbidity index.

123 A variety of machine learning models were developed, including generalized boosted 124 regression, random forest, and decision trees. An interaction depth of 3 and a total number of 500 125 trees were chosen, as was the type of the random forest and the regression model. The 126 classification/predictive performance was measured using the mean absolute percentage error 127 (MAPE), where a result of < 10% is classified as highly accurate, <20% denotes as a good forecast 128 20%-50% as a reasonable forecast and everything >50% as an inaccurate forecast (10). The MAPE 129 factor, also known as mean absolute percentage deviation (MAPD), is used for accuracy of a 130 forecasting prediction. Continuous data are reported as mean \pm standard deviation (SD) or 131 median (interquartile range (IQR)) and categorical data as numbers (percentages). 132 Hyperparameters were tuned, and the final model was selected based on the MAPE. The final 133 model chosen was the random forest model based on its superior performance.

The analysis was carried out using R version 4.0.4. The random forest library was used for the random forest models, the metrics library used for the calculation of the performance measurements, the gbm library for the generalized boosted regression models and the rpart library was used for the other models.

- 138 2.5 Deployment
- 139 The best performing model will be deployed as a web-based, user-friendly application using
- 140 RShiny to predict the final costs, that considers the different cost factors.
- 141 (Accessible via : <u>https://colonsurgerycost.shinyapps.io/Final_Cost/</u>).
- 142

143 3. Results

144 3.1 Cohort

A total of 347 patients were included in our study. This number consists of all patients from the center who suffered from the diagnosed factors of section 3 and had to undergo the type of operations mentioned. The mean age was 67 ± 14 years (range 28-94). 162 (47%) patients were male and 185 (53%) were female. Tables 1 and 2 provide all baseline variables and their descriptive statistics. Continuous variables were recorded as mean \pm SD (range) in Table 1.

150 Categorical variables were recorded as numbers (percentage) on Table 2. No missing 151 values were detected. Table 3 provides the variables' characteristics and descriptive statistics that 152 are not mentioned in Table 1 or Table 2 and are based on their impact on the final costs.

153

Variable	Overall (n)	Mean (SD)	Min	Max	Range	Median (IQR)
Age	347	67 (14)	28	94	66	68
Hospital days	347	9 (10)	1	84	83	5
ICU days	347	1 (5)	0	70	70	0
Operation time	347	175 (102)	23	1.280	1.257	154
Anesthesia time	347	119 (90)	45	1.020	997	95
Final Cost	347	-32.502 (45.650)	-52.0591	-7.485	52.8076	-20.011
CCI	347	4 (3)	0	16	16	3
Table 1. Variable characteristics for continuous values.						

- 154 155
- 156

Variable	n (%)
Gender	
Male	162 (47%)
Female	185 (53%)

Insurance	
General	283 (82%)
Semi-Private	49 (14%)
Private	15 (4%)
Diagnosis	
Tumor	162 (47%)
Non-Tumor	185 (53%)
Emergency Surgery	
No	331 (95%)
Yes	16 (5%)
Operation	
Hartmann`s procedure	19 (5%)
Hemicolectomy left	16 (4%)
Extended Hemicolectomy left	6 (2%)
Hemicolectomy right	82 (24%)
Extended Hemicolectomy right	6 (2%)
Sigmoid resection	218 (63%)
Surgery approach	
Open	153 (44%)
Laparoscopic	194 (56%)
Anastomotic insufficiency	
No	331 (95%)
Yes	16 (5%)
ASA Score	
Ι	12 (4%)
II	184 (53%)
III	137 (39%)
IV	14 (4%)

¹⁵⁸

.

Table 2. Variable characteristics for categorical values.

¹⁵⁹

Variable	Overall (n)	Mean (SD)	Min	Max	Median (Q1, Q3)	P-Value
Insurance	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	0.643
General	283	-31.773 (47.490)	-520.591	-7.485	-18.433 (-27.464, -14.823)	
Semi-Private	49	-33.495 (27.892)	-192.811	-10.919	-22.645 (-40.043, -19.795)	
Private	15	-42.996 (57.232)	-241.331	-13.915	-23.979 (-39.017, -18.426)	
Diagnosis	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	0.842
Tumor	162	-33.025 (40.120)	-298.957	-7.485	-21.129 (-28.294, -15.790)	
Non-Tumor	185	-32.043 (50.098)	-52.059	-9.929	-19.155 (-29.688, -14.859)	
Operation	347	-32.502 (45.650)	-52.0591	-7.485	-20.011 (-28.828, -15.332)	< 0.001
Hartmann	19	-25.479 (20.230)	-75.676	-7.485	-18.433 (-24.551, -14.053)	

Hemicolectomy left	16	-65.777 (91.964)	-38.419	-15.045	-32.297 (-70.713, -18.876)	
Extended	6	-11.0698 (20122)	-520.591	-13.915	-28.751 (-46.173, -22.338)	
Hemicolectomy left						
Hemicolectomy right	82	-35135 (39.474)	-241.331	-10.665	-22.469 (-35.663, -16.468)	
Extended	6	-65.768 (114.464)	-298.957	-13.086	-17.726 (-29.401, -14.799)	
Hemicolectomy right						
Sigmoid resection	218	-26.613 (23.764)	-192.811	-9.379	-18.684 (-25.538, -15.180)	
Surgery approach	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	< 0.001
Open	153	-46.531 (64.486)	-520.591	-7.485	-25.989 (-45.758, -18.708)	
Laparoscopic	194	-21.437 (13.486)	-91.098	-9.379	-17.275 (-21.765, -14.685)	
Anastomotic	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	< 0.001
insufficiency						
No	331	-26.051 (20.763)	-192.811	-7.485	-19.472 (-27.204, -15.121)	
Yes	16	-165.941 (136.653)	-520.591	-27.444	114.158 (225.666, -78.015)	
ASA Score	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	< 0.001
Ι	12	-20.626 (5.177)	-30.208	-14.035	-20.982 (-23.627, -16.212)	
II	184	-23.129 (21.680)	-241.331	-7.485	-17.938 (-22.591, -14.515)	
III	137	-38.328 (44.857)	-384.159	-10.665	-22.645 (-43.274, -16.997)	
IV	14	-108.844 (140.598)	-520.591	-20.280	-53.515 (-79.035, -33.144)	

160

100

Table 3. Descriptive statistics based on final costs.

161

162

163 3.2 Model Performance

During internal validation, the performance of all three models was tested and stated with 164 their mean value and their 95% confidence intervals (Table 3). The random forest classifier 165 provided the highest MAPE for predicting the final costs (21.4). Thus, it was the model with the 166 167 best internal validation performance and was subsequently used for predicting costs (11). In 168 comparison, the decision tree and general boosted regression model displayed results for MAPE of only 25.5 and 29.7, respectively. Therefore, the average of the MAPE for the final costs is around 169 170 21.4 which means that on average, the forecast of this prediction model regarding the final costs 171 are off by 21.4%. Since a MAPE value of <20% is considered as being "good", our result is showing 172 decent results. The percentage of the random forest classifier's variance, which was explained in 173 the models, varied from 73.81% to 81.05%. Specific feature importance according to the random 174 forest classifier is displayed as Gini Index in Figure 1, while Figure 2 shows the prediction of the 175 Random Forest Classifier compared to the actual observed values from the test data set for the 176 final cost factor.



181 182

178

179

180

183 In Figure 1, one can see those factors such as LOS and anastomotic insufficiency as well as 184 intensive care unit stay are the best predictors in our model, which could be explained as being 185 variables that are often correlated with post-operative complications and thus being more costly. 186 The factor of hospitalization can be explained as being a good predictor of cost because the overall 187 costs for a hospital will increase if the patient is not progressing after surgery. The same can be 188 said about the intensive care unit. For the anastomotic insufficiency cases, it is evident as well 189 that these complications bare a higher burden on the final costs. Mean decrease in Gini is the 190 mean of a variable's total decrease in node impurity, weighted by the proportion of samples 191 reaching that node in each individual decision tree in the random forest. A higher mean decrease 192 in Gini indicates higher variable importance. In other words, a node impurity is a measure of how 193 much the model error increases when a particular variable is randomly permuted or shuffled.

Figure 2 indicates that the predicted values are not far off the actual observed values based on our data set. For most of the observations, our model was able to perform decently in predicting the final costs.

Figure 3 displays the Bland-Altman plot. The following information can be derived visually from the diagram: (1) an estimate of the true value on the x-axis (mean) (2) standard deviation (3) whether and to what extent systematic measurement errors (bias) lead to the deviations (variability was eliminated by difference formation on y-axis) (4) whether the deviation of the methods or the dispersion of the deviation depends on the level of the measured

values (5) and whether outliers are present. Based on the plot one can imply that the values are

- 203 mostly well distributed and not many outliers occur.
- 204



Figure 2. Predicted vs. Real observations of the model (Ground Truth).

206

207



227 examined. Typically, MAPE is a measure of error. It is used to measure the accuracy of a forecast 228 (12). In calculating MAPE, the difference between the actual value and the forecast value is 229 determined and expressed as a percentage. This means that if the difference between the actual 230 value and the forecast value is small, the percentage is small (13). On the other hand, if the 231 difference between the actual value and the forecast value is large, MAPE percentage is large. 232 This implies that a small MAPE percent is an indication of the forecast value being near the actual 233 value. In other words, the forecast value is more accurate (14). In the case of the three models, 234 since the random forest model had the lowest MAPE percent value for all the costs compared to the other models considered, it is the most effective model in predicting the cost. 235

236 Why is Random Forest the most effective predictive model compared to the decision tree 237 and generalized boosted regression models? This question can be answered by examining the 238 model. The random forest model is a machine learning technique that is used to solve 239 classification and regression problems (15). This model uses ensemble learning, a technique that 240 combines many classifiers to obtain solutions to complex problems. A random forest algorithm 241 comprises of multiple decision trees. The forest that is generated by the algorithm is trained 242 through bootstrap aggregating or bagging (16). Bagging is a meta-algorithm that improves the machine learning algorithms' accuracy. 243

The random forest algorithm establishes the result from the predictions of decision trees. It predicts by taking the mean of the prediction output of the various trees (17). This implies that the predicted outcome by the algorithm becomes more accurate when the number of decision trees is increased.

One of the features of the random forest model that makes it more accurate in predicting cost outcomes, is it reduces the overfitting problem normally experienced when using the decision tree model. As indicated, the model uses an ensemble learning method based on bagging (15, 18). In other words, the model creates many decision trees and then considers the outcomes of all the trees in its final prediction, enhancing the accuracy of the prediction by the model.

253 However, despite the higher accuracy of the random forest model when compared to the 254 decision tree and generalized boosted regression models, the model does not have the highest 255 possible accuracy when considered alone. Normally, when examining the accuracy of a 256 prediction using MAPE, the result of less than 10% is considered highly accurate. A MAPE score 257 of less than 20% denotes a good forecast, while that between 20 and 50% is considered a reasonable forecast (12). Looking at the results, it shows that the random forest model gives 258 259 mostly reasonable forecasts rather than accurate forecasts. The model gave an outcome of over 20% when analyzed using the MAPE. This means that while it is the most accurate model when 260 261 compared to the other models, when considered alone, it has only considerable accuracy and it 262 does not accurately predict the cost incurred.

A number of similar studies have been carried out on the random forest model in terms of its accuracy in predicting outcomes. For example, Mei et al. (2014) examined the prediction accuracy of the random forest model when applying real-time forecasting of the New York electricity market (18). In reviewing the model's prediction accuracy, its results were compared

to that of the auto-regressive-moving-average model and an artificial neural network model. It 267 268 was established that the random forest model exhibited a lower MAPE value. The results in the study by Mei et al. (2014) are similar to those of this study which also show that the random forest 269 270 model has a higher level of making fewer mistakes by predicting when compared to other studies 271 (18). However, the shortcoming of the study by Mei et al. (2014) is it compares the random forest 272 model to only two other models. This does not provide adequate insight into the model's prediction accuracy (18). A comparison with additional models would have helped determine 273 274 whether the random forest model was the most accurate prediction model or if others were more 275 accurate.

276 Another similar approach to comparing algorithms was made by Xu et al. (2021), which 277 developed and tested an accurate prediction model based on the random forest classification 278 algorithm (19). They evaluated the prediction for inland water quality. To evaluate the 279 performance of the model, the researchers compared it to other models: multilayer perceptron, 280 SVR (support vector regression), KNN (K-Nearest Neighbor), ridge regression, gradient boosting regression, bagging and decision tree. It was established that the random forest-based prediction 281 282 model had the highest level of accuracy when compared to all the other prediction models 283 examined. This implies that random forest provides the most accurate outcomes when used for 284 prediction. The results in the study by Wang et al. (2020) align with those of this study since it 285 was also established that the random forest model is the most accurate compared to other models. 286 The study by Wang et al. (2020) provides better insight into the accuracy of the random forest 287 model because it compared it to multiple models (19). It is an indication that the random forest 288 model is one of the most accurate prediction models that can be used to predict costs for surgery.

289 Lastly, the results are in line with those of Toqué et al. (2020), who also established that the 290 random forest model has a higher accuracy compared to other models (20). In the study, Toqué 291 et al. (2020) built and tested machine learning models for forecasting the Montreal subway smart 292 card entry logs using event data to find an optimal model that accurately predicts the number of 293 incoming passengers at each station of a transportation network (20). The prediction models were 294 random forest, gradient boosting decision trees, artificial neural networks and kernel-based 295 models, including a support vector regressor and a gaussian process (20). The results showed that 296 all the random forest models performed best using RMSE for the evaluation, and did decent using 297 MAPE and MAE.

The results in this study show that all the models have reasonable accuracy as the MAPE for each of all the costs highlighted is below 50%. This means that all of the models can be used to predict the costs to some level of accuracy. However, when compared it can be seen that the random forest model is a more accurate predictor. These results are evident in similar studies showing that the random forest model is a more accurate prediction model.

303 4.2 Implications

304 One of the implications of the results is that hospitals and other concerned parties can 305 employ the random forest model to forecast costs not only for colon surgery but also the costs of 306 other risks and conditions mentioned previously. This work lays the foundation for further work

307 and research in this area. This will allow for better financial calculations for hospitals. Through 308 such a predictive model, it is possible to better estimate medical costs, which is especially 309 important when factors such as LOS in the hospital and ICU as well as complications such as 310 anastomotic insufficiency can have a large financial impact on the high cost. The results show that the random forest model provides more accurate predictions compared to other models like 311 312 generalized boosted regression and decision tree models. It means that for concerned parties to 313 achieve more accurate results when predicting the costs of conditions or any other outcome, the 314 random forest model should be employed.

315 Another implication is that there is a need for further research about the model in terms of 316 enhancing the accuracy of the random forest model. The results show that for the final costs 317 examined, the accuracy is more than 20%. This is only reasonable accuracy. However, it is way 318 before the desired value. As indicated, the MAPE value of less than 20% is an indication of a good 319 forecast, while that of less than 10% shows that the forecast is highly accurate. While achieving a 320 highly accurate forecast is unlikely, any good prediction model should give a good forecast. With the random forest model being the most accurate model, this implies that it should be developed 321 322 further to improve accuracy as to give more credible results when used to predict outcomes, 323 meaning further research is needed on the model.

324 Despite the good implications and the wide range of applications, the ethical aspect should 325 not be ignored. Naik et al. have shown in their work that there are currently no well-defined 326 guidelines when it comes to treating people with an application such as this. They mention that 327 transparency must be created when working with such algorithms. Furthermore, weaknesses 328 such as cyberattacks and privacy invasion should not be ignored if you want to advance this field 329 and research (21).

330 4.3 Limitations of the study

331 The main limitation of the study is a lack of a representative sample. In this case, the focus 332 was on patients undergoing colon surgery. However, in the sample dataset, only 347 individuals 333 met this criterion. This implies that the sample was not selected in the manner that made it 334 representative of patients undergoing colon surgery. The larger the dataset, the more accurate the 335 results are. However, the limited number of individuals with common reasons for higher costs 336 implies that it was not possible to effectively test the developed models in terms of their ability 337 to predict costs associated with the disease. For such models, there is a need for adequate and detailed data to ensure they are tested thoroughly. Additionally, an overall increase in the sample 338 339 size could result in more precise models by looking at the values in Table 4. Especially the events 340 per predictor should be bigger.

341	I
011	

Table 4. Internal validation performance for the 3 developed models

	Classifier	MAPE (%) Final Costs
	Random Forest	21.4 (17.2-26.8)
	Decision Tree	25.2 (21.4-26.3)
	Generalized Boosted Regression	29.7 (25.2-34.2)
342	Note: Scores Reported as Mean (95% Confidence Interval)	

Note: Scores Reported as Mean (95% Confidence Interval)

343 5. Conclusion

344 Post-operative complications such as anastomotic insufficiency, ICU or hospital LOS 345 increase the cost burden for patients and hospitals. Also, preoperative conditions like CCI 346 increase cost. However, there is no way of predicting these costs so that a patient or healthcare 347 system can prepare adequately to handle the condition. This study thereby aimed to develop and 348 validate a prediction model to accurately predict cost and develop strategies to eliminate or cover them. Out of the three tested models, the results obtained based on MAPE analysis showed that 349 350 the random forest model is the most accurate. Therefore, the results imply this model should be adopted for prediction. However, the fact that MAPE results were mostly over 20% means that 351 352 further research should be undertake on improving its accuracy.

- 354 Author Contributions: Conceptualization A.T., B.E., data collection B.E.; analysis V.O., A.T.;
- 355 visualization A.T., writing-original draft preparation A.T, V.O.; writing-review and editing
- 356 D.F., M.D.H., P.C.C. All authors have read and agreed to the published version of the manuscript.
- 357 **Funding:** This research received no external funding.

358 **Data Availability Statement:** The datasets used and/or analysed during the current study are 359 available from the corresponding author on reasonable request.

- 360 **Conflicts of Interest:** The authors declare no conflicts of interest.
- 361

362 **References**

- Xi, Y. and Xu, P., 2021. Global colorectal cancer burden in 2020 and projections to
 2040. *Translational Oncology*, 14(10), p.101174.
- Soeters, P.B., de Zoete, J.P.J.G.M., Dejong, C.H.C., Williams, N.S. and Baeten, C.G.M.I., 2002.
 Colorectal surgery and anastomotic leakage. *Digestive surgery*, *19*(2), p.150.
- Karliczek, A., Harlaar, N.J., Zeebregts, C.J., Wiggers, T., Baas, P.C. and Van Dam, G.M., 2009.
 Surgeons lack predictive accuracy for anastomotic leakage in gastrointestinal surgery. *International journal of colorectal disease*, 24(5), pp.569-576.
- Kourou, K., Exarchos, T.P., Exarchos, K.P., Karamouzis, M.V. and Fotiadis, D.I., 2015.
 Machine learning applications in cancer prognosis and prediction. *Computational and* structural biotechnology journal, 13, pp.8-17.
- Mosavi, A., Ozturk, P. and Chau, K.W., 2018. Flood prediction using machine learning
 models: Literature review. *Water*, *10*(11), p.1536.
- Musunuri, B., Shetty, S., Shetty, D., Vanahalli, M., Pradhan, A., Naik, N., Paul, R., 2021.
 Acute-on-Chronic Liver Failure Mortality Prediction using an Artificial Neural Network.
 Engineered Science, 15, pp.187-196.
- Hameed, B.M.Z.; S. Dhavileswarapu, A.V.L.; Raza, S.Z.; Karimi, H.; Khanuja, H.S.; Shetty,
 D.K.; Ibrahim, S.; Shah, M.J.; Naik, N.; Paul, R.; Rai, B.P.; Somani, B.K. Artificial Intelligence
 and Its Impact on Urological Diseases and Management: A Comprehensive Review of the
 Literature. J. Clin. Med. 2021, 10, 1864.
- Collins, G.S., et al., Transparent reporting of a multivariable prediction model for individual
 prognosis or diagnosis (TRIPOD): the TRIPOD statement. 2015. 102(3): p. 148-158.
- Bolenz, Gupta, Roehrborn, Lotan, Predictors of costs for robotic assisted laparoscopic radical
 prostatectomy, Urologic Oncology: Seminars and Original Investigations, Volume 29, Issue
 3, 2011, Pages 325-329.
- Abidin, S. and Jaffar, M.M. (2014) Forecasting Share Prices of Small Size Companies in Bursa
 Malaysia. Applied Mathematics and Information Sciences, 8, 107-112
- 389 11. Sushmita, Newman, Marquardt, Ram, Prasad, De Cock, Teredesai, 2015. Population Cost
 390 Prediction on Public Healthcare Datasets. In Proceedings of the 5th International Conference
- 391 on Digital Health 2015. Association for Computing Machinery, New York, NY, USA, 87-94.

- 12. Coleman, C.D. and Swanson, D.A., 2007. On MAPE-R as a measure of cross-sectional
 estimation and forecast accuracy. *Journal of Economic and Social Measurement*, 32(4), pp.219233.
- 395 13. Hyndman, R.J. and Koehler, A.B., 2006. Another look at measures of forecast 396 accuracy. *International journal of forecasting*, 22(4), pp.679-688.
- Rayer, S., 2007. Population forecast accuracy: does the choice of summary measure of error
 matter?. *Population Research and Policy Review*, 26(2), pp.163-184
- Sinha, P., Gaughan, A.E., Stevens, F.R., Nieves, J.J., Sorichetta, A. and Tatem, A.J., 2019.
 Assessing the spatial sensitivity of a random forest model: Application in gridded population modeling. *Computers, Environment and Urban Systems*, 75, pp.132-145
- 402 16. Bharathidason, S. and Venkataeswaran, C.J., 2014. Improving classification accuracy based
 403 on random forest model with uncorrelated high performing trees. *Int. J. Comput.*404 *Appl*, 101(13), pp.26-30.
- 405 17. Wang, L., Liu, Z.P., Zhang, X.S. and Chen, L., 2012. Prediction of hot spots in protein
 406 interfaces using a random forest model with hybrid features. *Protein Engineering, Design &*407 Selection, 25(3), pp.119-126.
- I. Mei, D. He, R. Harley, T. Habetler and G. Qu, "A random forest method for real-time price
 forecasting in New York electricity market," 2014 IEEE PES General Meeting | Conference & *Exposition*, 2014, pp. 1-5.
- 411 19. Xu, J.; Xu, Z.; Kuang, J.; Lin, C.; Xiao, L.; Huang, X.; Zhang, Y. An Alternative to Laboratory
 412 Testing: Random Forest-Based Water Quality Prediction Framework for Inland and
 413 Nearshore Water Bodies. Water 2021, 13, 3262.
- 20. Toqué, F., Côme, E., Trépanier, M., Oukellou, F., 2020. Forecasting of the Montreal subway
 smart card entry logs with event data. *TRB*, *CIRRELT-2020-33*.
- 21. Naik N, Hameed BMZ, Shetty DK, Swain D, Shah M, Paul R, Aggarwal K, Ibrahim S, Patil
 V, Smriti K, Shetty S, Rai BP, Chlosta P and Somani BK (2022) Legal and Ethical
 Consideration in Artificial Intelligence in Healthcare: Who Takes Responsibility? *Front. Surg.*9:862322.
- 420