

1 **Developing and validating a multivariable prediction model for**
2 **predicting costs of colon surgery**

3 Anas Taha^{1,2,†}, Stephanie Taha-Mehlitz^{3,†}, Vincent Ochs¹, Bassey Enodien², Michael
4 Drew Honaker⁴, Daniel M. Frey^{2,††} and Philippe C. Cattin^{1,††}

5

6 1. Department of Biomedical Engineering, Faculty of Medicine, University of Basel,
7 Allschwill, Switzerland

8 2. Department of Surgery, GZO Hospital, Wetzikon, Switzerland

9 3. Clarunis, Department of visceral Surgery, University Center for Gastrotestinal and liver
10 Diseases, St. Clara Hospital, Basel Switzerland

11 4. Department of Surgical Oncology and Colorectal Surgery, East Carolina University,
12 Brody School of Medicine, Greenville, North Carolina, USA.

13 † These authors contributed equally to this work and share the first authorship.

14 †† These authors contributed equally to this work and share the last authorship.

15

16 Correspondence: anas.taha@unibas.ch

17

18

19

20 **Abstract**

21 Hospitals are burdened with predicting, calculating and managing various cost-affecting
22 parameters regarding patients and their treatments. Accuracy in cost prediction is further affected
23 if a patient suffers from other health issues which hinder the traditional prognosis. This can lead
24 to an unavoidable deficit in the final revenue of medical centers. This study aims to determine
25 whether machine learning (ML) algorithms can predict cost factors based on patients undergoing
26 colon surgery. For the forecasting, multiple predictors will be taken into the model to provide a
27 tool that can be helpful for hospitals to manage their costs which ultimately will lead to operating
28 more cost-efficiently. . This proof of principle will lay the groundwork for an efficient ML-based
29 prediction tool based on multicenter data from a range of international centers in the subsequent
30 phases of the study. With a % MAPE result of 18 – 25.6, our model's prediction showed decent
31 results to forecast the costs regarding various diagnosed factors and surgical approaches. There
32 is an urgent need for further studies on predicting cost factors, especially for cases with
33 anastomotic leakage, to minimize unnecessary costs for hospitals.

34

35 **1. Introduction**

36 1.1 Background

37 Colorectal cancer (CRC) is one of the most prevalent cancers in the world today based on
38 diagnoses, with about 1.8 million cases being diagnosed and about 0.7 million related deaths
39 occurring annually. In addition, CRC accounts for 10% of all newly diagnosed cancers, a
40 considerable social and economic burden for many nations worldwide (1). One of the treatment
41 modalities for colorectal cancer is surgery. Surgery is aimed at obtaining an adequate oncologic
42 resection while re-establishing intestinal continuity. Over time, there have been improvements in
43 the way the disease is treated. But existing patient comorbidities can limit the surgical procedures.
44 The time required to prepare patients for surgery and address their comorbidities contribute to
45 increased surgical costs. However, despite many improvements, significant other complications
46 still occur during, and especially after, a surgical procedure. To avoid this, the patient is placed
47 in necessary post-operative care, generally for 5 and 7 days after a surgical operation. Other post-
48 operative risk factors will further add to the surgical cost, but their prediction is very vague due
49 to the absence of sufficient datasets. These involve performing a colorectal anastomosis,
50 anastomotic leak, (2), delirium or prolonged ileus (3), other emergency surgeries, longer intra-
51 operative time, and peritoneal contamination

52 The comorbidities and longer stays result in a cost burden for patients and hospitals. This
53 is why prediction models are now being updated to determine the costs for anastomotic
54 insufficiency. Prediction models are normally used to estimate the probability of achieving a
55 particular outcome (4). A large number of prediction models have been developed, but only a
56 small number are used because not all models accurately predict the desired outcome (5). This

57 study focuses on developing and validating a multivariable prediction model to predict costs for
58 patients undergoing colon surgery while considering their stay in the hospital. This will help
59 determine the cost burden due to variable hospital length of stay (LOS) as well as days spent in
60 intensive care units (ICU). The medical context is prognostic in that it is focused on predicting
61 the cost of overall expenditure involved in colon surgery for the clinical center and the patient.

62 1.2 Rationale

63 The rationale for developing and validating the multivariable model is that it will help
64 accurately predict the costs associated with colon surgery. Accurate prediction will help patients
65 and practices employed by the hospital make more informed decisions, as well as aid in policies
66 enacted by the government. The results that come with the use of the model will also aid in
67 surgical planning. In short, developing and validating the multivariable model will provide
68 insight into costs involved in colon surgery. In turn, it will allow revisions in care and help
69 develop strategies for improved management. Similar studies for prediction purposes have been
70 conducted in the field of medicine. For example, Musunuri et al. have used machine learning in
71 the form of artificial intelligence to predict 90-day liver disease mortality. Focused on acute-on-
72 chronic liver failure, they achieved a model with an accuracy of 94.12% and an area under the
73 curve of 0.915 (6). Hameed et al. wrote about the impact of artificial intelligence on urological
74 diseases. In their literature review, they have pointed to multiple publications using various
75 models like support vector machine, nearest neighbour, random forrest, convolutional neural
76 network or artificial neural networks to predict and classify diseases like prostate cancer,
77 urothelial cancer, renal cancer or urolithiasis. What differs from those publications and their work
78 from ours is, that they use a classification model instead of a regression model. The most
79 important benefit of using a regression model compared to a classification model is that it helps
80 predict continuous values, whereas classification models try to predict discrete class labels. To
81 predict the costs associated with colon surgery in an accurate way, a machine learning regression
82 model is used. Using this approach. We aim to contribute to an existing gap in this field (7).

83 1.3 Objectives

- 84 • To develop prediction models for the final costs in patients based on multiple predictors.
- 85 • To test the models in terms of their ability to accurately predict the final costs associated
86 with colon surgery in patients.

87 2. Methods

88 2.1 Overview and Data Collection

89 Data was extracted from a registry of patients who underwent colonic anastomosis for
90 various reasons such as tumors, diverticulitis, mesenterial ischemia, iatrogenic or traumatic
91 perforation, or inflammatory bowel disease (aggregated as “non-tumor”) at the Hospital of
92 Wetzikon from 1st January 2013 to the 31st December of 2019. No patients were excluded from
93 the initial data collection. Furthermore, this study was completed based on the transparent
94 reporting of a multivariable prediction model for individual prognosis or diagnosis (TRIPOD)

95 statement checklist for prediction model development (8).

96 Utilizing this data, we developed a machine learning model to predict the costs of colon
97 surgery.

98 2.2 Ethical Considerations

99 The registry data was approved by an institutional review board, where the patients'
100 informed consent was waived. The study was registered at [Req 2021-01107].

101 2.3 Predictors and Outcome Measures

102 Recorded variables include Insurance (general/semi-private/private), age, surgical
103 procedure (Hartmann/left sided hemicolectomy and extended left sided hemicolectomy/ right
104 sided hemicolectomy and extended right sided hemicolectomy/sigmoid resection), surgical
105 approach (open/laparoscopic), diagnosis (tumor/non-tumor), final costs (the sum of all cost
106 factors), length of stay (in days), Intensive care stay (in days), operation time (in minutes),
107 anaesthesia time (in minutes), ASA-Score (I,II,III,IV), gender (male/female), CCI (Charlson
108 Comorbidity Index), anastomotic insufficiency and emergent/non-emergent. The data on the
109 final cost, which is the sum of all the costs incurred during the stay in hospital for surgery, were
110 collected in CHF (Swiss Francs). Other cost factors not incorporated since they add up to the final
111 costs include administrative costs, costs of hospitality, nurse costs, costs of infrastructure, doctor
112 costs, medical costs, operational costs, anesthesia costs and care costs.

113 2.4 Model Development

114 Data was randomly split into two sets, 80% of the data was put into a training set to build
115 the models and 20% was utilized for a test set to validate the models and assess their performance
116 internally. The two sets had approximately the same class distribution (Gaussian). The following
117 14 predictors were chosen to predict the final costs based on regression and clinical insights: age,
118 gender, insurance, diagnosis, operation, surgical approach, hospitalization, intensive care,
119 surgical procedure and anaesthesia time, CCI, ASA-Score, anastomotic insufficiency and
120 emergency surgery (9).

121 By having variables included, such as the CCI and the ASA-Score, we are able to cover a
122 large number of diseases that are included in the comorbidity index.

123 A variety of machine learning models were developed, including generalized boosted
124 regression, random forest, and decision trees. An interaction depth of 3 and a total number of 500
125 trees were chosen, as was the type of the random forest and the regression model. The
126 classification/predictive performance was measured using the mean absolute percentage error
127 (MAPE), where a result of < 10% is classified as highly accurate, <20% denotes as a good forecast
128 20%-50% as a reasonable forecast and everything >50% as an inaccurate forecast (10). The MAPE
129 factor, also known as mean absolute percentage deviation (MAPD), is used for accuracy of a
130 forecasting prediction. Continuous data are reported as mean \pm standard deviation (SD) or
131 median (interquartile range (IQR)) and categorical data as numbers (percentages).
132 Hyperparameters were tuned, and the final model was selected based on the MAPE. The final
133 model chosen was the random forest model based on its superior performance.

134 The analysis was carried out using R version 4.0.4. The random forest library was used for
135 the random forest models, the metrics library used for the calculation of the performance
136 measurements, the gbm library for the generalized boosted regression models and the rpart
137 library was used for the other models.

138 2.5 Deployment

139 The best performing model will be deployed as a web-based, user-friendly application using
140 RShiny to predict the final costs, that considers the different cost factors.

141 (Accessible via : https://colonsurgerycost.shinyapps.io/Final_Cost/).

142

143 3. Results

144 3.1 Cohort

145 A total of 347 patients were included in our study. This number consists of all patients from
146 the center who suffered from the diagnosed factors of section 3 and had to undergo the type of
147 operations mentioned. The mean age was 67 ± 14 years (range 28-94). 162 (47%) patients were
148 male and 185 (53%) were female. Tables 1 and 2 provide all baseline variables and their
149 descriptive statistics. Continuous variables were recorded as mean \pm SD (range) in Table 1.

150 Categorical variables were recorded as numbers (percentage) on Table 2. No missing
151 values were detected. Table 3 provides the variables' characteristics and descriptive statistics that
152 are not mentioned in Table 1 or Table 2 and are based on their impact on the final costs.

153

Variable	Overall (n)	Mean (SD)	Min	Max	Range	Median (IQR)
Age	347	67 (14)	28	94	66	68
Hospital days	347	9 (10)	1	84	83	5
ICU days	347	1 (5)	0	70	70	0
Operation time	347	175 (102)	23	1.280	1.257	154
Anesthesia time	347	119 (90)	45	1.020	997	95
Final Cost	347	-32.502 (45.650)	-52.0591	-7.485	52.8076	-20.011
CCI	347	4 (3)	0	16	16	3

154 Table 1. Variable characteristics for continuous values.

155

156

157

Variable	n (%)
Gender	
Male	162 (47%)
Female	185 (53%)

Insurance	
General	283 (82%)
Semi-Private	49 (14%)
Private	15 (4%)
Diagnosis	
Tumor	162 (47%)
Non-Tumor	185 (53%)
Emergency Surgery	
No	331 (95%)
Yes	16 (5%)
Operation	
Hartmann`s procedure	19 (5%)
Hemicolectomy left	16 (4%)
Extended Hemicolectomy left	6 (2%)
Hemicolectomy right	82 (24%)
Extended Hemicolectomy right	6 (2%)
Sigmoid resection	218 (63%)
Surgery approach	
Open	153 (44%)
Laparoscopic	194 (56%)
Anastomotic insufficiency	
No	331 (95%)
Yes	16 (5%)
ASA Score	
I	12 (4%)
II	184 (53%)
III	137 (39%)
IV	14 (4%)

158 Table 2. Variable characteristics for categorical values.

159

Variable	Overall (n)	Mean (SD)	Min	Max	Median (Q1, Q3)	P-Value
Insurance	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	0.643
General	283	-31.773 (47.490)	-520.591	-7.485	-18.433 (-27.464, -14.823)	
Semi-Private	49	-33.495 (27.892)	-192.811	-10.919	-22.645 (-40.043, -19.795)	
Private	15	-42.996 (57.232)	-241.331	-13.915	-23.979 (-39.017, -18.426)	
Diagnosis	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	0.842
Tumor	162	-33.025 (40.120)	-298.957	-7.485	-21.129 (-28.294, -15.790)	
Non-Tumor	185	-32.043 (50.098)	-52.059	-9.929	-19.155 (-29.688, -14.859)	
Operation	347	-32.502 (45.650)	-52.0591	-7.485	-20.011 (-28.828, -15.332)	<0.001
Hartmann	19	-25.479 (20.230)	-75.676	-7.485	-18.433 (-24.551, -14.053)	

Hemicolectomy left	16	-65.777 (91.964)	-38.419	-15.045	-32.297 (-70.713, -18.876)	
Extended Hemicolectomy left	6	-11.0698 (20122)	-520.591	-13.915	-28.751 (-46.173, -22.338)	
Hemicolectomy right	82	-35135 (39.474)	-241.331	-10.665	-22.469 (-35.663, -16.468)	
Extended Hemicolectomy right	6	-65.768 (114.464)	-298.957	-13.086	-17.726 (-29.401, -14.799)	
Sigmoid resection	218	-26.613 (23.764)	-192.811	-9.379	-18.684 (-25.538, -15.180)	
Surgery approach	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	<0.001
Open	153	-46.531 (64.486)	-520.591	-7.485	-25.989 (-45.758, -18.708)	
Laparoscopic	194	-21.437 (13.486)	-91.098	-9.379	-17.275 (-21.765, -14.685)	
Anastomotic insufficiency	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	<0.001
No	331	-26.051 (20.763)	-192.811	-7.485	-19.472 (-27.204, -15.121)	
Yes	16	-165.941 (136.653)	-520.591	-27.444	114.158 (225.666, -78.015)	
ASA Score	347	-32.502 (45.650)	-520.591	-7.485	-20.011 (-28.828, -15.332)	<0.001
I	12	-20.626 (5.177)	-30.208	-14.035	-20.982 (-23.627, -16.212)	
II	184	-23.129 (21.680)	-241.331	-7.485	-17.938 (-22.591, -14.515)	
III	137	-38.328 (44.857)	-384.159	-10.665	-22.645 (-43.274, -16.997)	
IV	14	-108.844 (140.598)	-520.591	-20.280	-53.515 (-79.035, -33.144)	

160 Table 3. Descriptive statistics based on final costs.


161

162

163 3.2 Model Performance

164 During internal validation, the performance of all three models was tested and stated with
 165 their mean value and their 95% confidence intervals (Table 3). The random forest classifier
 166 provided the highest MAPE for predicting the final costs (21.4). Thus, it was the model with the
 167 best internal validation performance and was subsequently used for predicting costs (11). In
 168 comparison, the decision tree and general boosted regression model displayed results for MAPE
 169 of only 25.5 and 29.7, respectively. Therefore, the average of the MAPE for the final costs is around
 170 21.4 which means that on average, the forecast of this prediction model regarding the final costs
 171 are off by 21.4%. Since a MAPE value of <20% is considered as being “good”, our result is showing
 172 decent results. The percentage of the random forest classifier's variance, which was explained in
 173 the models, varied from 73.81% to 81.05%. Specific feature importance according to the random
 174 forest classifier is displayed as Gini Index in Figure 1, while Figure 2 shows the prediction of the
 175 Random Forest Classifier compared to the actual observed values from the test data set for the
 176 final cost factor.

177



178

179

180 Figure 1. Total decrease in node impurities, measured by the Gini index from splitting on the
181 variable, averaged over all trees.

182


183 In Figure 1, one can see those factors such as LOS and anastomotic insufficiency as well as
184 intensive care unit stay are the best predictors in our model, which could be explained as being
185 variables that are often correlated with post-operative complications and thus being more costly.
186 The factor of hospitalization can be explained as being a good predictor of cost because the overall
187 costs for a hospital will increase if the patient is not progressing after surgery. The same can be
188 said about the intensive care unit. For the anastomotic insufficiency cases, it is evident as well
189 that these complications bare a higher burden on the final costs. Mean decrease in Gini is the
190 mean of a variable's total decrease in node impurity, weighted by the proportion of samples
191 reaching that node in each individual decision tree in the random forest. A higher mean decrease
192 in Gini indicates higher variable importance. In other words, a node impurity is a measure of how
193 much the model error increases when a particular variable is randomly permuted or shuffled.

194 Figure 2 indicates that the predicted values are not far off the actual observed values based
195 on our data set. For most of the observations, our model was able to perform decently in
196 predicting the final costs.

197 Figure 3 displays the Bland-Altman plot. The following information can be derived
198 visually from the diagram: (1) an estimate of the true value on the x-axis (mean) (2) standard
199 deviation (3) whether and to what extent systematic measurement errors (bias) lead to the
200 deviations (variability was eliminated by difference formation on y-axis) (4) whether the
201 deviation of the methods or the dispersion of the deviation depends on the level of the measured

202 values (5) and whether outliers are present. Based on the plot one can imply that the values are
203 mostly well distributed and not many outliers occur.

204




205

206

Figure 2. Predicted vs. Real observations of the model (Ground Truth).

207



208

209

210 Figure 3. Bland-Altman Plot, measured by the difference of both measured values ($S1 - S2$) plotted on the
211 Y-axis against the mean value ($(S1 + S2) / 2$) on the X-axis.

212

213

214

215 4. Discussion

216 Cost and finances play an increasingly important role in today's healthcare system. It is
217 imperative that hospitals control their costs more accurately beforehand and estimate the
218 expenditure so that they do not get into financial difficulties.

219 Especially in surgery, and specifically colon surgery, this predictive model allows us to better
220 manage and optimize the process in front of the surgeon and hospital.

221

222 4.1 Interpretation of results

223 As indicated, in this study, three models were developed and tested. The results show that
224 random forest has the lowest percentage for all the costs examined on MAPE.

225 The lowest MAPE percentage for the random forest model indicates that this model is the
226 most accurate at predicting costs associated with surgeries compared to the other two models

227 examined. Typically, MAPE is a measure of error. It is used to measure the accuracy of a forecast
228 (12). In calculating MAPE, the difference between the actual value and the forecast value is
229 determined and expressed as a percentage. This means that if the difference between the actual
230 value and the forecast value is small, the percentage is small (13). On the other hand, if the
231 difference between the actual value and the forecast value is large, MAPE percentage is large.
232 This implies that a small MAPE percent is an indication of the forecast value being near the actual
233 value. In other words, the forecast value is more accurate (14). In the case of the three models,
234 since the random forest model had the lowest MAPE percent value for all the costs compared to
235 the other models considered, it is the most effective model in predicting the cost.

236 Why is Random Forest the most effective predictive model compared to the decision tree
237 and generalized boosted regression models? This question can be answered by examining the
238 model. The random forest model is a machine learning technique that is used to solve
239 classification and regression problems (15). This model uses ensemble learning, a technique that
240 combines many classifiers to obtain solutions to complex problems. A random forest algorithm
241 comprises of multiple decision trees. The forest that is generated by the algorithm is trained
242 through bootstrap aggregating or bagging (16). Bagging is a meta-algorithm that improves the
243 machine learning algorithms' accuracy.

244 The random forest algorithm establishes the result from the predictions of decision trees.
245 It predicts by taking the mean of the prediction output of the various trees (17). This implies that
246 the predicted outcome by the algorithm becomes more accurate when the number of decision
247 trees is increased.

248 One of the features of the random forest model that makes it more accurate in predicting
249 cost outcomes, is it reduces the overfitting problem normally experienced when using the
250 decision tree model. As indicated, the model uses an ensemble learning method based on bagging
251 (15, 18). In other words, the model creates many decision trees and then considers the outcomes
252 of all the trees in its final prediction, enhancing the accuracy of the prediction by the model.

253 However, despite the higher accuracy of the random forest model when compared to the
254 decision tree and generalized boosted regression models, the model does not have the highest
255 possible accuracy when considered alone. Normally, when examining the accuracy of a
256 prediction using MAPE, the result of less than 10% is considered highly accurate. A MAPE score
257 of less than 20% denotes a good forecast, while that between 20 and 50% is considered a
258 reasonable forecast (12). Looking at the results, it shows that the random forest model gives
259 mostly reasonable forecasts rather than accurate forecasts. The model gave an outcome of over
260 20% when analyzed using the MAPE. This means that while it is the most accurate model when
261 compared to the other models, when considered alone, it has only considerable accuracy and it
262 does not accurately predict the cost incurred.

263 A number of similar studies have been carried out on the random forest model in terms of
264 its accuracy in predicting outcomes. For example, Mei et al. (2014) examined the prediction
265 accuracy of the random forest model when applying real-time forecasting of the New York
266 electricity market (18). In reviewing the model's prediction accuracy, its results were compared

267 to that of the auto-regressive-moving-average model and an artificial neural network model. It
268 was established that the random forest model exhibited a lower MAPE value. The results in the
269 study by Mei et al. (2014) are similar to those of this study which also show that the random forest
270 model has a higher level of making fewer mistakes by predicting when compared to other studies
271 (18). However, the shortcoming of the study by Mei et al. (2014) is it compares the random forest
272 model to only two other models. This does not provide adequate insight into the model's
273 prediction accuracy (18). A comparison with additional models would have helped determine
274 whether the random forest model was the most accurate prediction model or if others were more
275 accurate.

276 Another similar approach to comparing algorithms was made by Xu et al. (2021), which
277 developed and tested an accurate prediction model based on the random forest classification
278 algorithm (19). They evaluated the prediction for inland water quality. To evaluate the
279 performance of the model, the researchers compared it to other models: multilayer perceptron,
280 SVR (support vector regression), KNN (K-Nearest Neighbor), ridge regression, gradient boosting
281 regression, bagging and decision tree. It was established that the random forest-based prediction
282 model had the highest level of accuracy when compared to all the other prediction models
283 examined. This implies that random forest provides the most accurate outcomes when used for
284 prediction. The results in the study by Wang et al. (2020) align with those of this study since it
285 was also established that the random forest model is the most accurate compared to other models.
286 The study by Wang et al. (2020) provides better insight into the accuracy of the random forest
287 model because it compared it to multiple models (19). It is an indication that the random forest
288 model is one of the most accurate prediction models that can be used to predict costs for surgery.

289 Lastly, the results are in line with those of Toqué et al. (2020), who also established that the
290 random forest model has a higher accuracy compared to other models (20). In the study, Toqué
291 et al. (2020) built and tested machine learning models for forecasting the Montreal subway smart
292 card entry logs using event data to find an optimal model that accurately predicts the number of
293 incoming passengers at each station of a transportation network (20). The prediction models were
294 random forest, gradient boosting decision trees, artificial neural networks and kernel-based
295 models, including a support vector regressor and a gaussian process (20). The results showed that
296 all the random forest models performed best using RMSE for the evaluation, and did decent using
297 MAPE and MAE.

298 The results in this study show that all the models have reasonable accuracy as the MAPE
299 for each of all the costs highlighted is below 50%. This means that all of the models can be used
300 to predict the costs to some level of accuracy. However, when compared it can be seen that the
301 random forest model is a more accurate predictor. These results are evident in similar studies
302 showing that the random forest model is a more accurate prediction model.

303 4.2 Implications

304 One of the implications of the results is that hospitals and other concerned parties can
305 employ the random forest model to forecast costs not only for colon surgery but also the costs of
306 other risks and conditions mentioned previously. This work lays the foundation for further work

307 and research in this area. This will allow for better financial calculations for hospitals. Through
308 such a predictive model, it is possible to better estimate medical costs, which is especially
309 important when factors such as LOS in the hospital and ICU as well as complications such as
310 anastomotic insufficiency can have a large financial impact on the high cost. The results show
311 that the random forest model provides more accurate predictions compared to other models like
312 generalized boosted regression and decision tree models. It means that for concerned parties to
313 achieve more accurate results when predicting the costs of conditions or any other outcome, the
314 random forest model should be employed.

315 Another implication is that there is a need for further research about the model in terms of
316 enhancing the accuracy of the random forest model. The results show that for the final costs
317 examined, the accuracy is more than 20%. This is only reasonable accuracy. However, it is way
318 before the desired value. As indicated, the MAPE value of less than 20% is an indication of a good
319 forecast, while that of less than 10% shows that the forecast is highly accurate. While achieving a
320 highly accurate forecast is unlikely, any good prediction model should give a good forecast. With
321 the random forest model being the most accurate model, this implies that it should be developed
322 further to improve accuracy as to give more credible results when used to predict outcomes,
323 meaning further research is needed on the model.

324 Despite the good implications and the wide range of applications, the ethical aspect should
325 not be ignored. Naik et al. have shown in their work that there are currently no well-defined
326 guidelines when it comes to treating people with an application such as this. They mention that
327 transparency must be created when working with such algorithms. Furthermore, weaknesses
328 such as cyberattacks and privacy invasion should not be ignored if you want to advance this field
329 and research (21).

330 4.3 Limitations of the study

331 The main limitation of the study is a lack of a representative sample. In this case, the focus
332 was on patients undergoing colon surgery. However, in the sample dataset, only 347 individuals
333 met this criterion. This implies that the sample was not selected in the manner that made it
334 representative of patients undergoing colon surgery. The larger the dataset, the more accurate the
335 results are. However, the limited number of individuals with common reasons for higher costs
336 implies that it was not possible to effectively test the developed models in terms of their ability
337 to predict costs associated with the disease. For such models, there is a need for adequate and
338 detailed data to ensure they are tested thoroughly. Additionally, an overall increase in the sample
339 size could result in more precise models by looking at the values in Table 4. Especially the events
340 per predictor should be bigger.

341 Table 4. Internal validation performance for the 3 developed models

Classifier	MAPE (%) Final Costs
Random Forest	21.4 (17.2-26.8)
Decision Tree	25.2 (21.4-26.3)
Generalized Boosted Regression	29.7 (25.2-34.2)

342 Note: Scores Reported as Mean (95% Confidence Interval)

343 **5. Conclusion**

344 Post-operative complications such as anastomotic insufficiency, ICU or hospital LOS
345 increase the cost burden for patients and hospitals. Also, preoperative conditions like CCI
346 increase cost. However, there is no way of predicting these costs so that a patient or healthcare
347 system can prepare adequately to handle the condition. This study thereby aimed to develop and
348 validate a prediction model to accurately predict cost and develop strategies to eliminate or cover
349 them. Out of the three tested models, the results obtained based on MAPE analysis showed that
350 the random forest model is the most accurate. Therefore, the results imply this model should be
351 adopted for prediction. However, the fact that MAPE results were mostly over 20% means that
352 further research should be undertake on improving its accuracy.

353

354 **Author Contributions:** Conceptualization A.T., B.E., data collection B.E.; analysis V.O., A.T.;
355 visualization A.T., writing—original draft preparation A.T, V.O.; writing—review and editing
356 D.F., M.D.H., P.C.C. All authors have read and agreed to the published version of the manuscript.

357 **Funding:** This research received no external funding.

358 **Data Availability Statement:** The datasets used and/or analysed during the current study are
359 available from the corresponding author on reasonable request.

360 **Conflicts of Interest:** The authors declare no conflicts of interest.

361

362 **References**

- 363 1. Xi, Y. and Xu, P., 2021. Global colorectal cancer burden in 2020 and projections to
364 2040. *Translational Oncology*, 14(10), p.101174.
- 365 2. Soeters, P.B., de Zoete, J.P.J.G.M., Dejong, C.H.C., Williams, N.S. and Baeten, C.G.M.I., 2002.
366 Colorectal surgery and anastomotic leakage. *Digestive surgery*, 19(2), p.150.
- 367 3. Karliczek, A., Harlaar, N.J., Zeebregts, C.J., Wiggers, T., Baas, P.C. and Van Dam, G.M., 2009.
368 Surgeons lack predictive accuracy for anastomotic leakage in gastrointestinal
369 surgery. *International journal of colorectal disease*, 24(5), pp.569-576.
- 370 4. Kourou, K., Exarchos, T.P., Exarchos, K.P., Karamouzis, M.V. and Fotiadis, D.I., 2015.
371 Machine learning applications in cancer prognosis and prediction. *Computational and*
372 *structural biotechnology journal*, 13, pp.8-17.
- 373 5. Mosavi, A., Ozturk, P. and Chau, K.W., 2018. Flood prediction using machine learning
374 models: Literature review. *Water*, 10(11), p.1536.
- 375 6. Musunuri, B., Shetty, S., Shetty, D., Vanahalli, M., Pradhan, A., Naik, N., Paul, R., 2021.
376 Acute-on-Chronic Liver Failure Mortality Prediction using an Artificial Neural Network.
377 *Engineered Science*, 15, pp.187-196.
- 378 7. Hameed, B.M.Z.; S. Dhavileswarapu, A.V.L.; Raza, S.Z.; Karimi, H.; Khanuja, H.S.; Shetty,
379 D.K.; Ibrahim, S.; Shah, M.J.; Naik, N.; Paul, R.; Rai, B.P.; Somani, B.K. Artificial Intelligence
380 and Its Impact on Urological Diseases and Management: A Comprehensive Review of the
381 Literature. *J. Clin. Med.* **2021**, *10*, 1864.
- 382 8. Collins, G.S., et al., Transparent reporting of a multivariable prediction model for individual
383 prognosis or diagnosis (TRIPOD): the TRIPOD statement. 2015. 102(3): p. 148-158.
- 384 9. Bolenz, Gupta, Roehrborn, Lotan, Predictors of costs for robotic assisted laparoscopic radical
385 prostatectomy, *Urologic Oncology: Seminars and Original Investigations*, Volume 29, Issue
386 3, 2011, Pages 325-329.
- 387 10. Abidin, S. and Jaffar, M.M. (2014) Forecasting Share Prices of Small Size Companies in Bursa
388 Malaysia. *Applied Mathematics and Information Sciences*, 8, 107-112
- 389 11. Sushmita, Newman, Marquardt, Ram, Prasad, De Cock, Teredesai, 2015. Population Cost
390 Prediction on Public Healthcare Datasets. In *Proceedings of the 5th International Conference*
391 *on Digital Health 2015*. Association for Computing Machinery, New York, NY, USA, 87-94.

- 392 12. Coleman, C.D. and Swanson, D.A., 2007. On MAPE-R as a measure of cross-sectional
393 estimation and forecast accuracy. *Journal of Economic and Social Measurement*, 32(4), pp.219-
394 233.
- 395 13. Hyndman, R.J. and Koehler, A.B., 2006. Another look at measures of forecast
396 accuracy. *International journal of forecasting*, 22(4), pp.679-688.
- 397 14. Rayer, S., 2007. Population forecast accuracy: does the choice of summary measure of error
398 matter?. *Population Research and Policy Review*, 26(2), pp.163-184
- 399 15. Sinha, P., Gaughan, A.E., Stevens, F.R., Nieves, J.J., Sorichetta, A. and Tatem, A.J., 2019.
400 Assessing the spatial sensitivity of a random forest model: Application in gridded population
401 modeling. *Computers, Environment and Urban Systems*, 75, pp.132-145
- 402 16. Bharathidasan, S. and Venkataeswaran, C.J., 2014. Improving classification accuracy based
403 on random forest model with uncorrelated high performing trees. *Int. J. Comput.*
404 *Appl*, 101(13), pp.26-30.
- 405 17. Wang, L., Liu, Z.P., Zhang, X.S. and Chen, L., 2012. Prediction of hot spots in protein
406 interfaces using a random forest model with hybrid features. *Protein Engineering, Design &*
407 *Selection*, 25(3), pp.119-126.
- 408 18. J. Mei, D. He, R. Harley, T. Habetler and G. Qu, "A random forest method for real-time price
409 forecasting in New York electricity market," *2014 IEEE PES General Meeting | Conference &*
410 *Exposition*, 2014, pp. 1-5.
- 411 19. Xu, J.; Xu, Z.; Kuang, J.; Lin, C.; Xiao, L.; Huang, X.; Zhang, Y. An Alternative to Laboratory
412 Testing: Random Forest-Based Water Quality Prediction Framework for Inland and
413 Nearshore Water Bodies. *Water* 2021, 13, 3262.
- 414 20. Toqué, F., Côme, E., Trépanier, M., Oukellou, F., 2020. Forecasting of the Montreal subway
415 smart card entry logs with event data. *TRB, CIRRELT-2020-33*.
- 416 21. Naik N, Hameed BMZ, Shetty DK, Swain D, Shah M, Paul R, Aggarwal K, Ibrahim S, Patil
417 V, Smriti K, Shetty S, Rai BP, Chlosta P and Somani BK (2022) Legal and Ethical
418 Consideration in Artificial Intelligence in Healthcare: Who Takes Responsibility? *Front. Surg.*
419 9:862322.
- 420