Environmental monitoring of Legionella

1	Environmental monitoring of Legionella in constructed water systems				
2	Samara Bin Salem ¹ , Abdullah Siddiqui ¹ , and Premanandh Jagadeesan* ¹ ,				
4					
5	1. Central Testing Laboratories,				
6	Quality and Conformity Council				
7	P.O Box 853, Abu Dhabi, United Arab Emirates				
8	Abu Dhabi, United Arab Emirates				
9					
10	*Corresponding Author: jpremanandh@gmail.com				
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					

Environmental monitoring of Legionella

26 Abstract

27 Legionella is an opportunistic pathogen found in aquatic environments having 28 significance. Policy regulation profound health mandates environmental 29 monitoring for prevention and control of *Legionella* spp. in different types of water 30 systems. The current study reports the trends of environmental monitoring of 31 Legionella in constructed water system from the Emirate of Abu Dhabi. Sample 32 collection and processing were performed as per standard procedures. A total of 33 8849 samples have been utilized during the 5 years study period of which 653 34 (7.4%) samples were positive for *Legionella* spp. The presence and frequency of 35 different serogroups are presented. The relationship between residual chlorine 36 levels and the presence of Legionella are discussed. The data indicates that 37 most positive Legionella cases occur with residual chlorine levels of less than 0.2 38 mg/L while higher chlorine concentrations are associated with fewer Legionella-39 positive cases. In conclusion, environmental monitoring is very important 40 to assess the trends of water quality for any remedial measures.

42

43

Key words: *Legionella* spp; environmental monitoring, residual chlorine, colony
forming units; actionable limit; serogroup

46

47

Environmental monitoring of Legionella

49 Introduction

Legionella is an opportunistic pathogen found naturally in the environments. Presence of *Legionella* in aquatic environments is of profound health significance as the exposure may lead to Legionnaires' disease, a severe form of pneumonia, and Pontiac fever, a milder illness resembling the flu. The disease can be fatal at times, particularly for immunocompromised individuals and people with chronic illnesses [1].

56 As a result, regulators across the globe have established management programs 57 on an ad hoc basis or mandated routine monitoring by law. Guidelines have been developed to provide frameworks for risk assessment, management, and 58 59 prevention strategies tailored to different types of water systems [2]. For 60 instance, the World Health Organization (WHO), recommended water safety plan 61 (WSP) which includes specifications for construction and commissioning of building water systems [3]. However, the guideline lacks threshold limits for 62 63 Legionella unlike other microbial pathogens in water [4]. While guidelines are 64 usually advisory and not necessarily prompt enforcement, the European Union Drinking Water Directive mandates monitoring of Legionella bacteria in all 65 66 drinking water distribution systems, including large domestic water and industrial 67 distribution systems. The parametric value of Legionella was <1000 CFU/L above 68 which resampling should be performed and screened for L. pneumophila [5]. In the 69 USA, there are no nationwide regulations for *Legionella* management [6].

70 Nevertheless, Center for disease control (CDC) has recommended a

Environmental monitoring of Legionella

71 multifactorial approach as performance indicator interpretation. Accordingly, 72 detection of up to 0.9 CFU/mL in a few of many tested locations within a water 73 system is considered well controlled. The facility is considered as poorly 74 controlled when more than 1CFU – 9.9 CFU/ml is found and above 10 CFU/ml is 75 uncontrolled in potable water [7].

In Abu Dhabi, United Arab Emirates (UAE), the department of energy is the 76 77 competing authority responsible for setting policy, standards and regulation for 78 the energy sector which includes water. The regulation states a comprehensive 79 risk assessment and periodic monitoring as effective means to ensure water 80 safety which specifies a zero tolerant policy for wholesome water [8]. In the case 81 of health care sector, all healthcare facilities are mandated to comply with water 82 quality testing twice a year and notify Abu Dhabi Public Health Center (ADPHC) 83 of any positive results. The current study aims to report the status of 84 environmental monitoring of Legionella in constructed water system from the 85 Emirate of Abu Dhabi.

86 Materials and Methods

87 Sample collection

Samples were collected in accordance with BS 7592:2022. Briefly, one liter of pre-flush samples was collected immediately after a tap or fitting is opened while dip samples were collected by immersing 1-L sterile container into a body of water depending on the sample source. All presterilized sample bottles contained 0.01% sodium thiosulfate to neutralize residual chlorine. The samples were

Environmental monitoring of Legionella

93 labelled and transported in insulated containers to the laboratory for culture
94 analysis as per ISO 11731-2: 2017.

96

97 Sample Processing

98 Water samples were concentrated by membrane filtration using polycarbonate 99 filters with a porosity of 0.2 µm. The filters were then transferred onto plates of 100 the chosen culture medium selective for Legionella (BCYE Agar) and incubated at 37 ±1°C for 7-10 days. After the incubation period, morphologically 101 102 characteristic colonies on the selective culture media were regarded as 103 presumptive Legionella and were subjected to subculture to demonstrate their 104 growth requirement for L-cysteine and iron (III) and species identification by 105 LATEX agglutination. The confirmed number of Legionella were reported as 106 colony forming units (CFU) of Legionella sp. or serogroups.

107 Residual Chlorine

For the detection of residual chlorine, dpd (diethyl paraphenylene diamine) indicator test is applied. The colorimetric method measures the intensity of color produced when dpd reacts with residual chlorine. The intensity of the color produced is proportional to the concentration of the chlorine in the sample. The results are expressed as mg/l with two decimal points.

113 Statistical Analysis

A descriptive statistical analysis was performed using Microsoft Excel. Nonparametric Mann–Whitney U test was conducted to establish the correlation

Environmental monitoring of Legionella

between Legionella and residual chlorine (expressed in mg/L). The statistical results were interpreted at the level of significance p < 0.05.

118 **Results and discussion**

Sampling and testing are the crucial step through which the effectiveness of water quality maintenance procedure is verified. Therefore, regulatory authorities enforce periodic monitoring of Legionella to assess the status in the Emirate of Abu Dhabi. While new rapid method such as real-time PCR analysis are best suited for well managed containment zones, culture is still regarded as the "gold standard" despite long incubation period as it provides concentration of cultivable *Legionella* which aids in risk management [9].

126 A total of 8849 samples have been utilized during the 5 years study period. The 127 samples were taken from either taps or cistern of the respective collection 128 location. Out of the 8849 samples collected, 653 (7.4%) samples were positive 129 for Legionella spp. Further analysis revealed L. pneumophila serogroup 2-14 with 130 a frequency of 19.6% while *L. pneumophila* serogroup 1 was found only in 2.8% 131 of all positive samples. The number of samples analyzed during the study period 132 and percentage of positive samples are presented in fig.1. It is evident from the 133 results that *Legionella* persists in some sampling locations. Nevertheless, only 33 134 samples (0.4%) were in the range of 100-800 cfu/L while the remaining samples 135 were between of 1-99 cfu/L (Table. 1). The actionable threshold of Legionella 136 varies ranging from 10² to 10⁵ cfu/L in potable water across Europe, UK and USA 137 [10]. Since Abu Dhabi has adapted a zero tolerant policy, any presence of 138 Legionella requires disinfection-based control measures to curb colonization. The

Environmental monitoring of Legionella

infective dose of *Legionella* is a subject of debate [11] and hence such stringent
measures are deemed necessary especially when there is no known safe level
of *Legionella* in the water systems.

142 As far as the residual chlorine levels are concerned, there is a statistically 143 significant difference between Legionella-positive and Legionella-negative 144 samples (p-value < 0.05). The median chlorine level in Legionella-positive 145 samples (0.1200 mg/L) is notably lower than in Legionella-negative samples 146 (0.2260 mg/L). The analysis strongly suggests an inverse relationship between 147 residual chlorine levels and the presence of Legionella in water samples. For 148 instance, higher chlorine levels are associated with a lower likelihood of 149 Legionella presence. The data indicates that most positive Legionella cases 150 occur with residual chlorine levels less than 0.2 mg/L. As the chlorine 151 concentration increases, the number of positive cases decreases, with the lowest 152 number of cases in the category with chlorine levels of 0.5 mg/L (Fig. 2). This 153 trend suggests that higher chlorine levels are associated with fewer Legionella-154 positive cases. The results signify the role of residual chlorine in the disinfection 155 process and control of Legionella in constructed water bodies. The result from 156 the study corroborates with previous studies on effective chlorine levels [12, 13] 157 and reinstates the need of monitoring and maintaining the residual chlorine 158 between 0.2-0.5 mg/L [8]. The stringent guality monitoring by both water and 159 health care regulators mandating testing regime every 6 months has been a 160 crucial tool to ensure the delivery of safe and good quality water to consumers.

161 **Concluding remarks**

Environmental monitoring of Legionella

A positivity rate of 7.4% has been observed over the study period with a surge in 2023 and 2024 emphasizing the impact of environmental monitoring of constructed water systems. This study further confirms the significance of maintaining residual chlorine between 0.2-0.5 mg/L as an effective means to control *Legionella* as recommended by the regulator. However, further investigation should reveal the resilience of these organism especially in areas where adequate concentration of chlorine is maintained.

169

170 Acknowledgments

The authors gratefully acknowledge the support and encouragement of the Abu Dhabi Quality and Conformity Council. Gratitude is also extended to the management of Central Testing Laboratories (CTL) for invaluable support.

174

175 **References**

- 176 1. Viasus, D., Gaia, V., Manzur-Barbur, C. et al. 2022. Legionnaires' Disease:
- 177 Update on Diagnosis and Treatment *Infect Dis Ther*, **11**: 973–986.
 178 https://doi.org/10.1007/s40121-022-00635-7
- 179 2. Sciuto, E., L, Laganà, P., Filice, S., Scalese, S., Libertino, S., Corso, D., Faro,
- 180 G., and Coniglio, M. A. 2021. Environmental Management of Legionella in
- 181 Domestic Water Systems: Consolidated and Innovative Approaches for
- 182 Disinfection Methods and Risk Assessment. *Microorganisms*, 9(3):577.
- 183 3. World Health Organization. 2007. Legionella and the prevention of
 184 legionellosis. World Health Organization. https://iris.who.int/handle/10665/43233

Environmental monitoring of Legionella

4. Van Kenhove E, Dinne K, Janssens A, Laverge J. 2019. Overview and
comparison of Legionella regulations worldwide. *Am J Infect Control*, 47(8):968978.

5. European Parliament and of the Council. Directive (EU) 2020/2184 of the
European Parliament and of the Council of 16 December 2020 on the Quality of

190 Water Intended for Human Consumption. Official Journal of the European Union

191 (2020). p. 435.

192 6. National Academies of Sciences, Engineering, and Medicine; Health and 193 Medicine Division; Division on Earth and Life Studies; Board on Population 194 Health and Public Health Practice; Board on Life Sciences; Water Science and 195 Technology Board; Committee on Management of Legionella in Water Systems. 196 Management of Legionella in Water Systems. Washington (DC): National 197 Academies Press (US); 2019 Aug 14. 5, Regulations and Guidelines on 198 Legionella Control in Water Systems.

199 https://www.ncbi.nlm.nih.gov/books/NBK555112/

200 7. Centers for Disease Control and Prevention. (2017). Developing a water

201 management program to reduce Legionella growth and spread in buildings: A

202 practical guide to implementing industry standards

203 https://www.cdc.gov/legionella/maintenance/wmp-toolkit.html

8. Department of Energy. 2021. Water quality regulations (Fifth edition). Available

205 at: https://www.doe.gov.ae/-/media/Project/DOE/Department-Of-Energy/Media-

206 Center-Publications/Regulations/English/Water-Quality-Regulations-2021-

207 Edition-5.pdf

Environmental monitoring of Legionella

208	9. Díaz-Flores, A	Á.; Montero, J.C.; C	Castro, F.J.; Alejandres	, E.M.; Bayón, C.; Solís,
-----	-------------------	----------------------	--------------------------	---------------------------

- 209 I.; Fernández-Lafuente, R.; Rodríguez, G. 2015. Comparing methods of
- determining Legionella spp. in complex water matrices. *BMC Microbiol*, 15:1–9.
- 10. Hamilton, K. A., Hamilton, M. T., Johnson, W., Jjemba, P., Bukhari, Z.,
- LeChevallier, M., Haas, C. N., and Gurian, P. L. 2019. Risk-Based Critical
- 213 Concentrations of Legionella pneumophila for Indoor Residential Water Uses.
- 214 Environ Sci Technol, 53(8):4528-4541.
- 11. Nisar, M. A., Ros, K.E., Brown, M. H., Bentham, R., Best, G., Xi, J., Hinds, J.,
- and Whiley, H. 2023. Stagnation arising through intermittent usage is associated
- 217 with increased viable but non culturable Legionella and amoeba hosts in a
- hospital water system. *Front Cell Infect Microbiol*,13:1190631.
- 12. Doménech-Sánchez, A., Laso, E., and Albertí, S. 2022. Determination of
 Legionella spp. prevalence in Spanish hotels in five years. Are tourists really at
 risk? *Travel Medicine and Infectious Disease*, 46:102269.
- 13. Marras, L., Bertolino, G., Sanna, A., Carraro, V., and Coroneo, V. 2023. *Legionella* spp. Monitoring in the Water Supply Systems of Accommodation
 Facilities in Sardinia, Italy: A Two-Year Retrospective Analysis. *Int J Environ Res Public Health*, 20(18):6722.
- 226
- 227
- 228
- 229

Fig. 1




Fig. 2

