FID	IID	GENDER	CASE	AA_DRB1_71_32659935_R		AA_DRB1_70_32659938_Q		AA_DRB1_67_32659947_L		AA_DRB1_33_32660049		AA_DRB1_32_32660052		AA_DRB1_31_32660055_F		AA_DRB1_31_32660055_V	
FID_Example1	IID_Example1	2	1	A	A	A	P	A	P	N	N	H	H	P	P	A	A
FID_Example2	IID_Example2	2	1	P	A	P	P	P	P	H	H	Y	Y	P	P	A	A
FID_Example3	IID_Example3	2	1	P	A	P	P	P	P	H	N	Y	Y	A	P	A	A
FID_Example4	IID_Example4	2	1	P	A	A	P	A	P	N	N	H	Y	A	P	A	A
FID_Example5	IID_Example5	2	1	P	P	A	P	A	P	N	N	Y	Y	A	P	A	A

FID	AA_DRB1_30_32660058_Y		AA_DRB1_30_32660058_R		AA_DRB1_28_32660064_D		AA_DRB1_26_32660070_F		AA_DRB1_11_32660115_V		AA_DRB1_11_32660115_L		AA_DRB1_10_32660118_Q		AA_DRB1_10_32660118_E		AA_DRB1_9_32660121_E	
FID_Example1	P	P	A	A	P	P	A	P	A	A	A	A	A	A	A	A	P	P
FID_Example2	P	P	A	A	P	P	P	P	P	P	A	A	P	P	A	A	P	P
FID_Example3	A	P	A	A	A	P	A	P	P	A	P	A	P	P	A	A	A	P
FID_Example4	A	P	A	A	A	P	A	P	A	A	P	A	A	P	A	A	A	P
FID_Example5	A	A	A	A	A	A	A	P	A	A	P	A	P	P	A	A	A	A

FID	CODE10	CODE04	CODE01	IF10	IF04	IF01	CALL
FID_Example1	PP AA AA AA AA HH	PP AA AA AP PP PP NN	AA AP AP AA	0	0	0	N
FID_Example2	PP AA PP AA AA YY	PP PP PP PP PP PP HH	AA PP PP PA	0	IS04	0	SE
FID_Example3	AP AA PA AA AA YY	AP PP PA AP AP AP HN	PA PP PP PA	0	IS04	IS01	SE
FID_Example4	AP AA AA AA AA HY	AP AP AA AP AP AP NN	PA AP AP PA	0	0	IS01	SE
FID_Example5	AA AA AA AA AA YY	AA PP AA AP AA AP NN	PA AP AP PP	0	0	IS01	SE
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N
							N

GuesSE is the algorythm for inferring HLA shared-epitope status from the output of the HLA imputation software SNP2HLA v1.0.3.
Usage:
* Use plink to extract the required amino-acid calls from the SNP2HLA in .ped format.
*Paste the corresponding data in the GuesSE -- two columns for each imputed amino-acid call (one per "allele"). NB! The order of input AA data should match the order in the sheet. The input should begin with the standard .ped fields "IID","FID","GENDER" and "CASE" (see example entries).
* The output data is contained in columns "IF10", "IF04", "IF01" and "CALL" (where IF10, IF04, IF01 reflect imputed HLA types DRB1:10, DRB1:04 and DRB1:01; the "CALL" column represents the shared epitope positivity status of the individual).

Required AA positions from SNP2HLA (extracted as a plink .ped file)

AA_DRB1_71_32659935_R
AA_DRB1_70_32659938_Q
AA_DRB1_67_32659947_L
AA_DRB1_33_32660049
AA_DRB1_32_32660052
AA_DRB1_31_32660055_F
AA_DRB1_31_32660055_V
AA_DRB1_30_32660058_Y
AA_DRB1_30_32660058_R
AA_DRB1_28_32660064_D
AA_DRB1_26_32660070_F
AA_DRB1_11_32660115_V
AA_DRB1_11_32660115_L
AA_DRB1_10_32660118_Q
AA_DRB1_10_32660118_E
AA_DRB1_9_32660121_E