

**Table C1. Results of pairwise comparisons for comparing phase locking values (PLVs) measured at different electrode locations.** PLV1, PLVs calculated using Parameter set I; PLV2, PLVs calculated using Parameter set II; PLV3, PLVs calculated using Parameter set III.

	Electrode Pair	Estimate	Standard Error	Degree of Freedom	T Ratio	<i>p</i> Value
PLV1	E3 vs. E9	-0.05	0.03	29.0	-1.16	.39
	E3 vs. E15	-0.13	0.04	30.3	-3.48	<.01
	E3 vs. E21	-0.12	0.05	40.0	-2.46	.08
	E9 vs. E15	-0.09	0.02	27.2	-3.51	<.01
	E9 vs. E21	-0.08	0.04	36.5	-1.91	.24
	E15 vs. E21	0.00	0.03	30.8	0.24	.99
PLV2	E3 vs. E9	-0.03	0.02	30.0	-1.42	.50
	E3 vs. E15	-0.11	0.03	29.7	-3.59	.01
	E3 vs. E21	-0.11	0.04	37.5	-2.59	.06
	E9 vs. E15	-0.08	0.02	27.2	-3.57	.01
	E9 vs. E21	-0.08	0.04	35.4	-2.15	.16
	E15 vs. E21	0.00	0.03	31.2	0.10	1.00
PLV3	E3 vs. E9	-0.02	0.02	30.1	-1.03	.73
	E3 vs. E15	-0.08	0.02	28.2	-3.38	.01
	E3 vs. E21	-0.09	0.03	33.4	-2.67	.05
	E9 vs. E15	-0.06	0.02	26.6	-3.37	.01
	E9 vs. E21	-0.07	0.03	33.1	-2.29	.12
	E15 vs. E21	0.00	0.02	30.9	0.22	1.00